

DMack

Tyre Suppliers to the FIA World Rally Championship 2011 - 2014

2014 Truck and Bus Tyre Range

WRC
FIA WORLD RALLY
CHAMPIONSHIP



XR266

Steer



A steer tyre for use on good road conditions, especially suited for distances over 600km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
12 R22.5	18	152/149	L	3550	3250	930	17
295/80 R22.5	16	150/147	M	3350	3075	830	17

XR868

Drive



A drive axle tyre to suit all vehicles for highways and good road conditions. Suited for short to medium distances less than 400km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
8.25 R16	14	126/122	K	1700	1500	670	14.5
10 R20	18	149/146	K	3250	3000	930	16.5
11 R20	18	152/149	K	3550	3250	930	17
12 R20	18	154/151	K	3750	3450	830	17.5

XR278

Steer



A steer tyre for use on good road conditions, especially suited for distances over 600km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
315/80 R22.5	18	154/151	M	3750	3450	830	17
315/80 R22.5	20	161/154	J	4625	3750	900	17
11 R22.5	16	146/143	M	3000	2725	830	15

XR268

Drive



A drive axle tyre for use on good road conditions and especially for distances over 600km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
315/80 R22.5	18	154/151	K	3750	3450	830	22
12 R22.5	18	152/148	L	3550	3150	850	23

XR299

Drive



A drive axle tyre which can be used in all positions, suitable for all road conditions.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
315/80 R22.5	18	154/151	L	3750	3450	830	19
13 R22.5	18	154/151	L	3750	3450	830	20

XR288

Drive



A drive axle tyre and trailer tyre for good road conditions and especially for distances over 600km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
315/80 R22.5	20	161/154	G	4625	3750	900	21.5
11 R22.5	14	146/143	L	3000	2725	830	19
12 R22.5	18	152/148	L	3550	3150	850	23
13 R22.5	18	154/151	L	3750	3450	830	23

XR262

Drive



A drive axle tyre for highway use and good road conditions and especially for distances over 800km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
295/80 R22.5	16	150/147	M	3350	3075	830	21.5
315/80 R22.5	18	154/151	L	3750	3450	830	21.5
11 R22.5	16	146/143	M	3000	2725	830	16.5
12 R22.5	18	152/148	L	3550	3150	850	22.5
13 R22.5	18	154/151	L	3750	3450	830	18.5

GR100

Steer



Suitable for buses, steering axles on trucks and trailer axles on high quality roads. The pattern is designed for durability and long life especially for highway use.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
285/75 R24.5	16	147/144	M	3075	2800	830	15
295/75 R22.5	14	144/141	M	2800	2575	760	15
11 R24.5	14	146/143	M	3000	2725	720	14.5

XR758

Steer



A highway tyre which can be used on all axles and especially suited to long distance travel over 800km. This tyre features a high strength construction.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
10 R20	16	146/143	L	3000	2725	830	15
10 R20	18	149/146	L	3250	3000	930	15
11 R20	18	152/149	L	3550	3250	930	16

GR300

Drive



A drive axle tyre for use on normal roads. The tread pattern is designed to maximise grip, skid resistance and even tread wear.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
285/75 R24.5	16	147/144	K	3075	2800	830	22.5
295/75 R22.5	14	144/141	L	2800	2575	760	22.5
11 R24.5	14	146/143	M	3000	2725	720	22

XR518

Steer



A steer tyre for good road conditions and distances over 800km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
295/80 R22.5	18	152/149	K	3550	3250	900	16.5
10 R20	16	146/143	L	3000	2725	830	15.5
10 R20	18	149/146	L	3250	3000	930	15.5
11 R20	16	150/147	L	3350	3075	830	16
11 R20	18	152/149	L	3550	3250	930	16.5
12 R20	18	154/151	K	3750	3450	830	17.5

GR110

Steer



Suitable for buses, steering axles on trucks and trailer axles on high quality roads. The tread pattern is designed for durability and long life and superior highway performance.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
275/70 R22.5	16	148/145	M	3150	2900	900	14.5

GR120

Steer



Suitable for buses, steering axles on trucks and trailer axles on high quality roads. The tread pattern is designed for durability and long life and superior highway performance.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
215/75 R17.5	14	126/124	M	1700	1600	700	12.5
12 R22.5	18						12.5

XR818

Drive



Suitable for all tyre positions and road conditions. Developed for short to medium distances less than 600km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
9 R20	16	144/142	K	2800	2650	900	15.5
10 R20	16	146/143	K	3000	2725	830	16.5
10 R20	18	149/146	K	3250	3000	930	16.5
11 R20	18	152/149	K	3550	3250	930	17
12 R20	18	154/151	K	3750	3450	830	17.5

GR200

Trailer



An all purpose trailer tyre for highway and normal road use. The tyre has an improved heat emission layer built into the tread shoulder which greatly reduces heat generation.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
385/65 R22.5	20	160	J	4250	-	900	15.5

XR866

Drive



A drive axle tyre and trailer tyre for all vehicle types and road conditions. Suited for short distances less than 200km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
10 R20	16	146/143	K	3000	2725	830	17.5
10 R20	18	149/146	K	3250	3000	930	17.5
11 R20	18	152/149	K	3550	3250	930	19
12 R20	18	154/151	K	3750	3450	830	20.5

GR310

Drive



A drive axle tyre for all roads, the tread pattern is designed to maximise grip, skid resistance and even tread wear.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
215/75 R17.5	14	126/124	M	1700	1600	700	15
275/70 R22.5	16	148/145	M	3150	2900	900	15.5

XR518X

Drive



A tyre for all axles and vehicle types. Suited for short to medium distances less than 600km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
10 R20	18	149/146	K	3250	3000	930	15.5
11 R20	18	152/149	K	3550	3250	930	16.5
12 R20	18	154/151	K	3750	3450	830	17.5

XR898

Drive



A drive axle tyre and trailer tyre for all vehicles and road conditions. It is a good choice for short distances less than 200km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
10 R20	18	149/146	K	3250	3000	930	20.4

XR778

Drive



A drive axle tyre and trailer tyre for all road conditions. It is well suited for short distances less than 200km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
8.25 R16	16	128/124	K	1800	1600	770	17
8.25 R16	14	126/122	K	1700	1500	670	17

XR878

Drive



A drive axle tyre and trailer tyre for all vehicles and road conditions. It is suited for short distances less than 200km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
12 R20	18	154/151	G	3750	3450	830	21

XR798

Mining



Suited for all vehicles types used in industrial and mining applications. Use for short distances less than 100km and a good choice for dumper and loading trucks.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
10 R20	18	149/146	G	3250	3000	930	18.5
11 R20	18	152/149	G	3550	3250	930	19
12 R20	18	154/151	G	3750	3450	830	20.5

XR858

Drive



A drive axle tyre and trailer tyre for all vehicles and road conditions. It is suited for short distances less than 200km.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
10 R20	18	149/146	G	3250	3000	930	19
11 R20	18	152/149	G	3550	3250	930	19
12 R20	18	154/151	G	3750	3450	830	21

XR718

Mining



Suited for dumper vehicles travelling at low speed on extremely bad road conditions.

Size	Ply	Load	Speed	Max Load			Tread
				Single	Double	Pressure	Depth
295/80 R22.5	16	150/147	G	3350	3075	830	21
8.25 R16	16	128/124	K	1800	1600	770	17.5
10 R20	18	149/146	D	3250	3000	930	24
11 R20	18	152/149	D	3550	3250	930	25
12 R20	18	154/151	E	3750	3450	930	25

XR168

Drive



Used for all tyre positions on good and mixed road conditions. Especially suited for light truck and small bus and for dumper or agricultural vehicles

Size	Ply	Load	Speed	Max Load		Pressure	Tread
				Single	Double		Depth
7.5 R16	14	122/118	L	1500	1320	770	13.5
8.25 R16	14	126/122	L	1700	1500	670	13.5

XR188

Drive



Used for all tyre positions on dumper and light trucks which travel short distances and low speeds on extremely bad road conditions.

Size	Ply	Load	Speed	Max Load		Pressure	Tread
				Single	Double		Depth
7.5 R16	14	122/118	L	1500	1320	770	15.5
8.25 R16	16	128/124	K	1800	1600	770	15.5

XR198

Drive



Used for all tyre positions, especially light truck and bus, on good road conditions.

Size	Ply	Load	Speed	Max Load		Pressure	Tread
				Single	Double		Depth
7.5 R16	14	122/118	L	1500	1320	770	12.5
8.25 R20	14	136/134	K	2240	2120	830	15
8.25 R16	14	126/122	L	1700	1500	670	12.5
8.25 R16	16	148/124	L	1800	1600	770	12



Email:

Sales Office: sales@dmacktyres.com
Technical Support: technical@dmacktyres.com
Media Support: press@dmacktyres.com

Tel:

+44 1228 819954

DMACK, 42 Millbrook Road, Kingstown, Carlisle, England, CA3 0EU

www.dmacktyres.com